



CONSOLIDATED LAUNDRY MACHINERY

NapkinFaster

MODEL NF-1

FEATURES:

- Increases production of ironed napkins and other small items
- Operators need only feed the leading edge of items, the Napkin Faster does the rest
- Ensures consistent quality in all your small ironed goods
- Eliminates creases
- Fully adjustable including height, belt speed and vacuum



Five-lane NapkinFaster easily fits on the feed end of most ironers.

Feeding napkins and other small items into flatwork ironers can be one of the slowest and most inconsistent operations in any plant. That's why CLM has developed the NapkinFaster vacuum spreader/ feeder for napkins and other small items.

The NapkinFaster installs in minutes and easily fits on the feed end of most ironers. Once installed, the NapkinFaster will increase production of small items up to 25%, by minimizing loss of ironer capacity between items as occurs with normal hand feeding.

Operation of the NapkinFaster is easy, requiring no additional training or supervision. Operators simply place the leading edge of small items on the feed ribbons in the normal manner. The NapkinFaster takes over by spreading and straightening the linen as it enters the ironer, leaving operators free to quickly release the item and reach for the next one, even while the one already fed is still entering the ironer.

The NapkinFaster achieves its amazing results through the use of five individual, powerful vacuum chambers along with specially contoured stainless steel feed plates. Together, these features work to maximize ironer productivity while virtually eliminating creases.

The NapkinFaster is fully adjustable, allowing you to easily and quickly change the unit's height and suction power. Belt speed automatically changes to accommodate the speed of your ironer. With a NapkinFaster in place, you will increase production and item quality.

TECHNICAL SPECIFICATIONS:

OVERALL WIDTH

125 ¾"

OVERALL DEPTH

38"

OVERALL HEIGHT

41" to 52" (adjustable)

FEED TABLE WIDTH

119"

FEED TABLE DEPTH

32"

WEIGHT

900 pounds (net)
1050 pounds (shipping)

MOTORS

3 HP TEFC vacuum motor
½ HP TEFC drive motor

ELECTRICAL REQUIREMENT

208/230/460 Volts, 3 Ph., 60 cycle

CONTROLS

A dust-proof control box is mounted on the end of the NapkinFaster. Emergency stop button provided at east station. A start/stop button, speed control switch for suction motor, motor overload protection and inverters for each Motor are provided. Belt speed adjusts automatically.

Specifications subject to change without notice

CONSOLIDATED LAUNDRY MACHINERY
211 Erie Street, Pomona, CA 91768
T: (323) 232-2417 | F: (323) 231-8312
www.clmco.com