



**CONSOLIDATED  
LAUNDRY MACHINERY**

	<b>Model 105</b>	<b>Model 140</b>	<b>Model 165</b>	<b>Model 194</b>	<b>Model 264</b>	<b>Model 321</b>
Capacity, Dry weight (LBS)	200-285	300-450	450	400-600	600-800	1200
Machine Width	120"	120"	125"	135"	135"	151 ½"
Machine Depth, Level	91 ½"	101 ½"	106 ½"	104"	122"	122"
Minimum Dryer Spacing, center to center	156"	156"	162"	171"	171"	187 ½"
Exhaust Dust Connection Size	11" x 11"	15" x 15"	24" x 24"	24" x 24"	24" x 24"	24" x 24"
Basket Cubic Foot	105	140	165	194	264	321
Basket Diameter	65	65	70	79	79	85
Door Diameter	42"	42"	48"	48"	48"	60"
Blower Motor (HP)	10	15	15	25	25	30
Basket Motor (HP)	3	5	5	5	7.5	15
Tilt Angle Degrees	18	18	20	10	10	*
Outside Air Makeup	26"	26"	26"	30"	30"	32"
Lint Collector Outlet	18"	24"	24"	26"	26"	30"
Air Flow CFM	6,000	9,800	9,800	11,000	11,000	13,500
Electrical FLA @230V	60	70	70	80.5	87	120
Electrical FLA @480V	30	35	35	40.3	43.5	60
Water PSI	80	80	80	80	80	80
Air PSI	80	80	80	80	80	80

#### **GAS FIRED MODELS**

Gas WC Pressure	15"	15"	24"	15"	15"	15"
Burner Motor (HP)	1/3	3/4	3	3/4	3/4	3/4
Burner Rating mil. BTU/hr	1.5	1.95	2.5	2.7	27	3.5
Shipping Weight (LBS)	6,800	7,500	7,500	9,800	10,800	12,600

#### **STEAM MODELS**

Steam PSI Minimum	100	100	100	100	100	100
Shipping Weight (LBS)	6,800	7,800	7,800	10,100	11,100	12,900

#### **TUMBLE GREEN™ MODELS**

Burner Motor (HP)	3	3	3	3	3	3
Burner Rating Mil. BTU/hr	2.5	2.5	2.5	3	3	3.5
Tilt Angle	20	20	20	10	10	15
Gas WC Pressure	24"	24"	24"	24"	24"	24"
Shipping Weight (LBS)	6,500	7,500	7,500	9,800	10,800	12,600

For additional information please contact CLM by phone or email request to [sales@clmco.com](mailto:sales@clmco.com)

211 Erie Street. Pomona, CA 91768

Phone 323-232-2417 / Fax 323-231-8312

[www.clmco.com](http://www.clmco.com)